



480V 3% Impedance
240 Volts 6% Z - 480 Volts 3% Z - 600 Volts 2.4% Z - CE Marked
AC Line Reactor - Three Phase

1032



Catalog #: ALRB002TBC

PRODUCT FEATURES

- UR, cUR Recognized
- CE Marked
- Can be used with 208V, 240V, 480V, and 600V
- Gapped iron core with precision wound copper coils
- Compact design for more flexible installation
- Finger-safe terminal block
- Covered under Acme's 10 year limited warranty

BENEFITS

- Protects from damaging voltage drop
- Eliminates nuisance tripping
- Reduces surges and spike currents
- Longer life for motors and solid state components

UL STANDARD

UL 506

CSA STANDARD

C22.2 No 66

WARRANTY

Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

Primary Voltage:	240V / 480V / 600V
Frequency:	60 Hz
Impedance:	6% / 3% / 2.4%
Motor HP:	1
Motor Current:	2.1 A
Reactor Current:	2 A
Inductance:	11027 uH
Max Temperature Rise:	115°C
UL Insulation Class:	180°C

PRODUCT MEASUREMENTS

Height (In./cm):	3.875 (9.8)
Width (In./cm):	4.25 (10.8)
Depth (In./cm):	3.125 (7.9)

CONFIGURATION

Mounting Dimension (Depth):	2.00 (5.1)
Mounting Dimension (Width):	1.44 (3.7)

PACKAGING

Ship Weight (Lbs/Kg): 3 (1.4)

COMPLIANCES

UL Standard: UL 506
UL Listed: File E79947
CSA Standard: C22.2 No 66
CSA Listed: LR7357-16
CE: CE Marked
Warranty: Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf